(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 6 May 2005 (06.05.2005)

PCT

(10) International Publication Number WO 2005/041421 A1

(51) International Patent Classification7:

H03M 13/27

(21) International Application Number:

PCT/EP2004/010871

(22) International Filing Date:

29 September 2004 (29.09.2004)

(25) Filing Language:

٠

English

(26) Publication Language:

English

(30) Priority Data:


03021960.4 60/508,577 30 September 2003 (30.09.2003) EP 3 October 2003 (03.10.2003) US

- (71) Applicant (for all designated States except US): TELE-FONAKTIEBOLAGET L M ERICSSON (PUBL) [SE/SE]; S-164 83 Stockholm (SE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): SVENSSON, Mats [SE/SE]; Valdemars väg 98, S-224 74 Lund (SE).

- (74) Agent: STRÖM & GULLIKSSON IPC AB; P.O. Box 793, S-220 07 Lund (SE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, IP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: IN-PLACE DATA DEINTERLEAVING



(57) Abstract: A method for deinterleaving a sequence of interleaved data stored in a set of memory locations from a first order to a second order in-place of a memory with linear time. Two data items are withdrawn from the center of the sequence, creating a hole therein. Destination positions for said withdrawn data items are determined. It is determined whether the destination positions contain any data items. If so, the data items of said destination positions are replaced with the withdrawn data items, and second destination positions are determined for the data items withdrawn from the first destination positions. Otherwise, the first data items are inserted at the destination positions directly. If a data item is inserted at the hole of the sequence before the sequence is properly deinterleaved, an incorrect positioned data item is determined and repositioned. The repositioning sequence is repeated until all data items are correctly positioned.

O 2005/041421 A1

WO 2005/041421 A1



Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.